

PRODUCT SPECIFICATION SHEET INKJET PRINTING CANVASES

PRODUCT NAME:	TEMPO, 575SJ
ITEM MASTER:	TBD
CANVAS CONSTRUCTION:	65% polyester, 35% cotton base, 1 x 1 Weave
COATING:	One Acrylic Latex Primer Basecoat Semi-Matte Solvent Topcoat
ACIDITY (pH):	Neutral (Acid-free)
APPEARANCE:	Natural White, with medium texture
FINISH WEIGHT:	8.75 osy \pm 1.25 osy 296.0 gsm \pm 42.0 gsm
THICKNESS:	15.50 mils \pm 1.0 mils 393.50 microns \pm 25.5 microns
COLOR: (X-Rite 938 Spectrodensitometer, D ₅₀ ²)	
Whiteness	77.00 minimum
Brightness	80.00 minimum
L	92.50 minimum
a	0.00 nominal
b	0.00 nominal
SPECTRAL GLOSS, 60°: (Byk-Gardner Micro Tri-gloss)	44.0 nominal

This canvas is designed for digital printing applications using solvent based ink sets. Although designed for all printers using these ink sets, actual results may vary depending on printer model, age, print design, environmental conditions, and other factors. Exposure of a print to atmospheric pollutants, or to temperature, humidity, and / or lighting extremes can result in fading, color shifting, or other visual changes. The ideal conditions for printing and storage are a temperature of 70°F \pm 5°F and relative humidity of 50% RH \pm 3% RH.